

Finally,
the answer to
LCD protection.


We like to call
it, armor.

ARMR200

Vikuiti™ Anti-Reflection Matte Removable Film

LCD displays are extremely fragile. Screen damage costs both time and money, from warranty costs to repair time. Vikuiti™ Anti-Reflection Matte Removable Film ARMR200 helps protect LCD screens from damage and features advanced anti-reflection properties that improve viewing on LCD screens.

- **Durable** — helps protect display from scratches and scuffs
- **Anti-reflective coating** — helps improve clarity and readability
- **Easy to clean** — markers and fingerprints wipe away easily
- **Removable** — non-tacky adhesive removes easily with no residue
- **Matte surface** — for less slippage when writing with a stylus
- **Ultra thin** — ideal for screens requiring a stylus



ARMR200

Durable Protection. Removable Technology.



VIKUITI™ ANTI-REFLECTION MATTE REMOVABLE FILM [ARMR200]

**Protects delicate LCD screens from damage,
while improving clarity and readability.**

- **Optically clear, durable film** – helps provide non-permanent protection of LCDs
- **Ultra-thin multi-layer anti-reflection optical coatings** on the front surface minimize glare and increase clarity
- **Anti-soiling top layer** – easy to clean
- **Repels ink and even permanent markers** – wipes off easily with a lint-free cloth
- **Full surface adhesive** – no gaps or bunching
- **Durable hardcoat** – designed to last for up to 3 months, depending on use



Durable
may help reduce
repair/warranty costs




Vikuiti™ ARMR200
film is available in a
variety of sizes



Easy to apply –
non-tacky adhesive
applies smoothly

Anti-Fingerprint Layer
Anti-Reflection Coating
Matte Hardcoat
5 mil PET
1 mil Adhesive
Disposable Liner



Vikuiti™ Removable Anti-Reflection
Film's unique multilayered
construction reduces glare,
makes it easier to wipe off
fingerprints, and helps shield screens
from scratches and serious damage.

Colors on the various layers are for demonstration purposes only

N o m o n i a l f i l m p r o p e r t i e s

Thickness	Base ————— 5 mil
	Adhesive ——— 1 mil
Pencil Hardness	≥ 3H
Durability	10 rubs at 160g/in ²
Chemical Resistance	IPA, window cleaner, permanent marker, coffee
Environmental	Heat/Humidity — 65°C / 95% RH, 500 hrs
	Dry Heat ——— 85°C, 500 hrs
Specular Reflectance	≤ 1.1%
Transmission	≥ 92%
Gloss	75-110 gloss units
Typical values, not for specification purposes.	

3M

Optical Systems Division

3M Center, Building 275-6E-07
St. Paul, MN 55144-1000

We're easy to reach!

For more information, please visit our website at

www.3M.com/vikuiti/armr

or call Customer Service at

1-800-553-9215

Vikuiti and the Vikuiti "Eye"
symbol are trademarks of 3M.

Printed in U.S.A.

© 3M 2005 75-0500-5214-3